

CLICK VINYL FLOORING

TECHNICAL DATA SHEET



SUITABLE FOR
DAMP ROOMS



FIRE
RESISTANT




BUILT-IN INSULATION



EASY
MAINTENANCE

FINISHING



Embossed

DIMENSIONS AND TOLERANCES

Thickness (mm)	5,5mm
Length (cm)	121,92cm
Width (cm)	22,86cm
Tolerances	Width and Length $\pm 1,5\%$ Thickness $\pm 5\%$

MATERIAL

Composition	SPC (Stone Plastic Composite) Vinyl Floor with 4mm + 1.5mm IXPE foam			
Properties	Waterproof Abrasion resistance Comfortable Sound insulation			
Colours				
	Oak Prime	Countryside	Lullaby	Oak Dark

SPECIFICATIONS

Weight	2,224Kg/uni		
Wear layer	0,55mm		
Slip resistance	DS	EN 13893	
Fire behavior	Bfl-s1	EN 13501	
Dimensional stability	<0,12%	EN 434	
COVs	A+	ISO 16000	
Acoustic improvement	20dB	EN ISO 10140	
Abrasion resistance	1,8mm ³ /r	EN 660	
Indentation resistance	0,27mm	ISO 24343	
Usage class	Class 33	ISO 10874	
Electrical properties	0,1kV	EN 1815	
Anti-slip properties	R9	DIN 51130	
UV resistance	>6	ISO 105-B02	
Chemicals and stain resistance	Acetone	Did not affect the pavement	EN ISO 26987
	Coffee	Did not affect the pavement	EN ISO 26987
	- Sodium hydroxide solution (25%) - Caustic Soda (detergents)	Did not affect the pavement	EN ISO 26987
	- Hydrogen peroxide solution (30%) - Oxygenated water (detergents)	Did not affect the pavement	EN ISO 26987
	- Shoe polish	Did not affect the pavement	EN ISO 26987
Thermal conductivity	-5° - 0,079 W(m-K)	ISO 8301	
	40° - 0,097 W(m-K)		
Thermal resistance	-5° - 0,069 W(m-K)	ISO 8301	
	40° - 0,056 W(m-K)		

Notes: Its composition and appearance can change, while maintaining its behavior and performance.

The floor cannot be installed in a room that is more than 10 metres long or wide without creating an expansion joint.