

CLICK VINYL FLOORING



SUITABLE FOR
DAMP ROOMS



FIRE
RESISTANT




BUILT-IN INSULATION



EASY
MAINTENANCE

FINISHING








Embossed

DIMENSIONS AND TOLERANCES

Thickness (mm)	5,5mm
Length (cm)	122cm
Width (cm)	23cm
Tolerances	Width and Length $\pm 1,5\%$ Thickness $\pm 5\%$

MATERIAL

Composition	SPC (Stone Plastic Composite) Vinyl Floor with 4mm + 1.5mm IXPE foam				
Properties	Waterproof Abrasion resistance Comfortable Sound insulation				
Colours					
	Ash wood	Brown	Light grey	Grey	Dark brown

SPECIFICATIONS

Weight	2,224Kg/uni		
Wear layer	0,55mm		
Slip resistance	DS		EN 13893
Fire behavior	Bfl-s1		EN 13501
Dimensional stability	<0,12%		EN 434
COVs	A+		ISO 16000
Acoustic improvement	20dB		EN ISO 10140
Abrasion resistance	1,8mm ³ /r		EN 660
Indentation resistance	0,27mm		ISO 24343
Usage class	Class 33		ISO 10874
Electrical properties	0,1kV		EN 1815
Anti-slip properties	R9		DIN 51130
UV resistance	>6		ISO 105-B02
Chemicals and stain resistance	Acetone	Did not affect the pavement	EN ISO 26987
	Coffee	Did not affect the pavement	EN ISO 26987
	- Sodium hydroxide solution (25%) - Caustic Soda (detergents)	Did not affect the pavement	EN ISO 26987
	- Hydrogen peroxide solution (30%) - Oxygenated water (detergents)	Did not affect the pavement	EN ISO 26987
	- Shoe polish	Did not affect the pavement	EN ISO 26987
Thermal conductivity	-5° - 0,079 W(m-K)		ISO 8301
	40° - 0,097 W(m-K)		
Thermal resistance	-5° - 0,069 W(m-K)		ISO 8301
	40° - 0,056 W(m-K)		

Notes: Its composition and appearance can change, while maintaining its behavior and performance.

The floor cannot be installed in a room that is more than 10 metres long or wide without creating an expansion joint.