

MULTIFLEX

TECHNICAL DATA SHEET



COMMERCIAL
AREAS



GROUP
ACTIVITIES



SPORTS
FACILITIES

OTHER APPLICATIONS


PHYSIOTHERAPY - EXHIBITIONS - COMMON SPACES



FINISHING



Wood






Color

DIMENSIONS AND TOLERANCES

| | |
|--------------------------|--|
| Thickness (mm) | 4,5mm |
| Length - Roll (m) | 1,8m |
| Width - Roll (m) | 15m |
| Tolerances | Length & Width \pm 1,5% Thickness \pm 5% |

MATERIAL

| | | | |
|--------------------|---|--|---|
| Composition | PVC based synthetic flooring | | |
| Properties | UV resistance Resistance to compressive strength and impact forces Abrasion resistance Comfortable Acoustic insulation Non-slip Anti-bacterial | | |
| Colors |  |  |  |
| | Wood | Grey Wood | Grey |

ESPECIFICACIONES

| | | |
|-------------------------------------|------------------------------|-------------|
| Weight | 4,5mm: 3,75Kg/m ² | EN 430 |
| Shock absorption | 8mm: 39% | EN 14808 |
| Skid resistance | 97 | EN 13036-4 |
| Vertical ball behavior | 90% | EN 12235 |
| Vertical deformation | 8mm: 1,3mm | EN 14809 |
| Resistance to wear | 642mg | EN ISO 5470 |
| Resistance to indentation | 0,37mm | EN 1516 |
| Fire Behavior | A1fl | EN 13501 |
| Evenness | <0,2mm | EN 13036 |
| Resistance to a rolling load | 0,4mm | EN 1569 |
| PCP content | Does not contain PCP | |
| Formaldehyde emissions | E1 | EN 717 |

*With the reflection of light, small ripples can be seen.

*Its composition and appearance can change while maintaining its behavior and performance.