

MULTIFLEX

TECHNICAL DATA SHEET



COMMERCIAL
AREAS




SPORTS FACILITIES



GROUP
ACTIVITIES

FINISHING



Embossed

DIMENSIONS AND TOLERANCES

Thickness (mm)	4,5mm
Length - Roll (m)	0,9m
Width - Roll (m)	15m
Tolerances	Length & Width $\pm 1,5\%$ Thickness $\pm 5\%$

MATERIAL

Composition	Synthetic PVC flooring
Properties	UV resistance Resistance to compressive strength and impact forces Abrasion resistance Comfortable Acoustic insulation Non-slip Anti-bacterial
Colors	  Blue Grey

SPECIFICATIONS

Weight	4,5mm: 3,75Kg/m ²	EN 430
Shock absorption	8mm: 39%	EN 14808
Skid resistance	97	EN 13036-4
Vertical ball behavior	90%	EN 12235
Vertical deformation	8mm: 1,3mm	EN 14809
Resistance to wear	642mg	EN ISO 5470
Resistance to indentation	0,37mm	EN 1516
Fire Behavior	Bfl	EN 13501
Evenness	<0,2mm	EN 13036
Resistance to a rolling load	0,4mm	EN 1569
PCP content	Does not contain PCP	
Density	590Kg/m ²	
Formaldehyde emissions	E1	EN 717

Notes: Small ripples can be seen in the reflection of light.

Its composition and appearance can change, while maintaining its behaviour and performance.

To ensure the durability and good performance of the flooring, no sharp, heavy, hard or cutting objects should be used that could jeopardise the integrity of the material.