

VINYL FLOORING AND WALL COVERING WITH SPC DRY BACK

TECHNICAL SPECIFICATIONS



APPROPRIATE FOR BOTH FLOORS AND WALLS



RESISTANT TO FIRE, WATER, AND MOISTURE



VISUAL COHERENCE




EFFORTLESS UPKEEP

APPLICATION
INTERIOR



FINISHES



Relief






DIMENSIONS AND TOLERANCES - RECTANGULAR CONFIGURATION

Thickness (millimeters)	2mm
Length (millimeters)	914mm
Width (millimeters)	457mm
Box Weight	32,8Kg
Tolerances	Length and width $\pm 1.5\%$ Thickness $\pm 5\%$

DIMENSIONS AND TOLERANCES - SQUARE CONFIGURATION

Thickness (millimeters)	2mm
Length (millimeters)	610mm
Width (millimeters)	610mm
Box Weight	24,8Kg
Tolerances	Length and width $\pm 1.5\%$ Thickness $\pm 5\%$

COMPOSITION

Material	SPC vinyl flooring (plastic and stone composite) featuring a thickness of 2mm.			
Colors	914x457mm	 Terracotta	 Gray	 Travertine
	610x610mm	 White marble	 Obsidian marble	
Quantity per box	914x457 - 20 units 610x610 - 18 units			

Please note that while composition and appearance may vary, behavior and performance will remain consistent.