

# 5G CLICK VINYL FLOORING

## TECHNICAL SPECIFICATIONS



SUITABLE FOR  
DAMP ROOMS



FIRE  
RESISTANT



BUILT-IN INSULATION



EASY  
MAINTENANCE


## FINISHING



Embossed

## DIMENSIONS AND TOLERANCES

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| <b>Thickness (mm)</b> | 6mm                                                |
| <b>Length (cm)</b>    | 60cm                                               |
| <b>Width (cm)</b>     | 12cm                                               |
| <b>Tolerances</b>     | Width and Length $\pm 1,5\%$   Thickness $\pm 5\%$ |

|                    |                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------|
| <b>Composition</b> | SPC (Stone Plastic Composite) Vinyl Floor with 5mm + 1mm IXPE foam                               |
| <b>Properties</b>  | Waterproof   Abrasion resistance   Comfortable   Sound insulation   Easy to install              |
| <b>Colours</b>     | <br>Natural Oak |

|                               |                   |              |
|-------------------------------|-------------------|--------------|
| <b>Weight</b>                 | 0,454Kg/uni       |              |
| <b>Click system</b>           | Valingue 5G       |              |
| <b>Wear layer</b>             | 0,55mm            |              |
| <b>Slip resistance</b>        | DS                | EN 13893     |
| <b>Fire behavior</b>          | Bfl-s1            | EN 13501     |
| <b>Dimensional stability</b>  | <0,12%            | EN 434       |
| <b>COVs</b>                   | A+                | ISO 16000    |
| <b>Acoustic improvement</b>   | 19dB              | EN ISO 10140 |
| <b>Abrasion resistance</b>    | <0.015g (Class T) | EN 660-2     |
| <b>Indentation resistance</b> | ≤ 0.15mm          | ISO 24343    |
| <b>Usage class</b>            | Classe 33         | ISO 10874    |
| <b>Anti-slip properties</b>   | R9                | DIN 51130    |
| <b>UV resistance</b>          | >6                | ISO 105-B02  |

Notes: Its composition and appearance may vary, but its behaviour and performance remain the same.

The flooring must not be installed in a room more than 10 metres long or wide without providing an expansion joint.