

PRIMEFLEX

TECHNICAL DATA SHEET



COMMERCIAL
AREAS



LOBBIES AND
LOUNGES



GROUP
ACTIVITIES



FINISHING




Texture

DIMENSIONS AND TOLERANCES

Thickness (mm)	2mm
Length - Roll (m)	1m
Width - Roll (m)	10m
Tolerances	Length & Width $\pm 1,5\%$ Thickness $\pm 5\%$

MATERIAL

Composition	Synthetic PVC flooring					
Properties	UV resistance Resistance to compressive strength and impact forces Abrasion resistance Non-slip Anti-bacterial					
Colors						
	Pearl Grey	Mineral Taupe	Sage Green	Graphite Grey	Natural Oak	Nordic Oak

SPECIFICATIONS

Weight	33Kg/uni	
Wear Layer	0.3mm	
Slip Resistance	DS	EN 13893
Fire Resistance	Bfl-s1	EN 13501
Dimensional Stability	<0,12%	EN 434
VOCs	A+	ISO 16000
Anti-Slip Properties	R9	DIN 51130
PCP Concentration	PCP-Free	

Notes: Due to light reflection, slight ripples may be visible.

Its composition and appearance may change, but its behavior and performance remain the same.

To ensure the durability and proper performance of the flooring, do not use sharp, hard, or pointed objects that could compromise the integrity of the material.